

大功率可程式直流電源供應器



產品特點:

- ① 內建軟體校正輸出電壓電流功能.
- ② 內建 12Bit 數位 / 類比 轉換電路.
- ③ 鍵盤具有鎖定功能,避免誤觸按鍵.
- ④ 螢幕用繪圖型液晶顯示器(Graphic 240*128 dots).
- ⑤ 保護功能包含 OVP(過電壓)OCP(過電流)UCP(低電流).
- ⑥ 高穩定、低漣波、低雜訊輸出.
- ⑦ 輸出電壓具有微調按鍵.
- ⑧ 單鍵控制輸出 ON/OFF.
- ⑨ 可搭配 GP-IB & RS-232.
- ⑩ 可選配電壓回授補償線路
- ⑪ 計時器最高可設定 100 小時.
- ⑫ 可以將輸出電壓,電流,時間分組設定和儲存,可存 100 組.
- ⑬ 內建輸出 V,A,TIME 記錄功能,最多記錄 100 組.
- ⑭ 可以設定自動操作循環次數,最高可設 10000 次.
- ⑮ 可由 PLC 遙控輸出 ON/OFF.
- ⑯ 可由 PLC 監視輸出操作狀態



共同規格

型式		線性式		S C R 式		
規格						
Ripple & Noise		0.05%±3mvrms		≤0.5%		
Line Regulation		0.05%±3mvrms		≤1%		
Load Regulation		0.05%±5mvrms		≤1%		
Program Accuracy	Voltage	low range	≤60V 0.05% ±1count	low range	≤60V 0.05% ±1count	
		high range	>60V 0.1% ±1 count	high range	>60V 0.1% ±1 count	
Accuracy	Current	low range	≤60A 0.05% ±1count	low range	≤60A 0.05% ±1count	
		high range	>60A 0.1% ±1 count	high range	>60A 0.1% ±1 count	
Display Accuracy	Voltage	low range	≤60V 0.1% ±1 count	low range	≤60V 0.5% ±1count	
		high range	>60V 0.1% ±1 count	high range	>60V 0.5% ±1 count	
Accuracy	Current	low range	≤60A 0.5% ±1count	low range	≤60A 1% ±1count	
		high range	>60A 0.3% ±1 count	high range	>60A 1% ±1 count	
LCD Display		240*128 DOTS		240*128 DOTS		
Protection Setting		OVP / OCP / UCP		OVP / OCP / UCP		
Timer Setting		Max:100hour(1sec~99h)		Max:100hour(1sec~99h)		
Program Memory		Max:100Pionts		Max:100Pionts		
Operating Environment		0°C~40°C		0°C~40°C		
Interface		GP-IB(Option)、RS-232		GP-IB(Option)、RS-232		
AC Power Source		AC 1ø 110V/220V ±10% 50/60Hz		AC 3ø 220V/380V ±10% 50/60Hz		
Dimensions(W*H*D) (cm)	5U W43 *H24 *D54 (不含把手)		27U W43 *H135 *D66 (不含把手)			
	9U W43 *H44 *D54 (不含把手)		27U(L) W53 *H135 *D66 (不含把手)			
	16U W43 *H85 *D66 (不含把手)		27U(D) W86 *H135 *D66 (不含把手)			

型號一覽表

MODEL	O/P V	O/P A	DIMENSION	MODEL	O/P V	O/P A	DIMENSION
GP-3010HH	0-30V	0-100A	9U	GP-50H50	0-500V	0-5A	5U
GP-3020HH	0-30V	0-200A	16U	GP-50H10H	0-500V	0-10A	16U
GP-6050H	0-60V	0-50A	9U	GP-50H20H	0-500V	0-20A	27U
GP-6010HH	0-60V	0-100A	16U	GP-50H50H-3	0-500V	0-50A	27U(L)
GP-10H30H	0-100V	0-30A	9U	GP-50H10HH-3	0-500V	0-100A	27U(D)
GP-10H50H	0-100V	0-50A	16U	GP-60H10H	0-600V	0-10A	16U
GP-10H15HH-3	0-100V	0-150A	27U(L)	GP-60H20H	0-600V	0-20A	27U
GP-15H30H	0-150V	0-30A	9U	GP-60H50H-3	0-600V	0-50A	27U(D)
GP-15H50H	0-150V	0-50A	16U	GP-10HH20	0-1000V	0-2A	16U
GP-30H10H	0-300V	0-10A	9U	GP-10HH50	0-1000V	0-5A	27U
GP-30H20H	0-300V	0-20A	16U	GP-10HH10H	0-1000V	0-10A	9U
GP-30H50H	0-300V	0-50A	27U	GP-15HH20	0-1500V	0-2A	16U
GP-30H10HH-3	0-300V	0-100A	27U(L)	GP-15HH50	0-1500V	0-5A	9U

型號尾數為 (-3) 代表輸入電源為 3 相電源

★Consult the Factory THE Customer Specification / 接受特殊規格訂製

★Specificagions Subject to change without notice / 規格尺寸如有變更,不另行通知

固鼎電子企業有限公司

公司地址:新北市新店區寶興路 45 巷 9 弄 4 號 2 樓

電話:02-29150071~2 傳真:02-29117311 E-MAIL:gitek@ms33.hinet.net